



GENERAL NOTES:

1. EMBEDMENT OF CHAIN-LINK FABRIC SHALL VARY ACCORDING TO THE FOLLOWING SOIL CONDITIONS;
 - a. NON-CORROSIVE SOIL: 6" MINIMUM EMBEDMENT OF CHAIN-LINK FABRIC TO BE BURIED IN NATIVE SOIL. BURIED CHAIN-LINK FABRIC TO BE FOLDED/SLOPED TOWARDS THE INSIDE OF THE FACILITY.
 - b. CORROSIVE SOIL: 6" MINIMUM EMBEDMENT OF CHAIN-LINK FABRIC INTO 12" HEADER CURB POURED AROUND THE FENCE'S PERIMETER.

CONSTRUCTION KEY NOTES:

- A. 1 $\frac{7}{8}$ " O.D. PIPE (2.27 LB./FT.)
- B. 2 $\frac{3}{8}$ " O.D. PIPE (3.65 LB./FT.)
- C. 7 GA. COILED SPRING TENSION WIRE
- D. 2500 PSI CONCRETE
- E. 9 GA. GALVANIZED 2" CHAIN-LINK FABRIC
- F. BARBED TAPE, 24" COIL WITH 3 ROWS OF 3 STRAND BARBED WIRE
- G. 12" CONCRETE HEADER CURB POURED AROUND FENCE PERIMETER (SEE NOTE 1-b)
- H. LINE POST BARBED WIRE ARM (45°)

STANDARD
DETAIL

DATE: 4/1995
REV: 11/11/2009

CHAIN-LINK FENCE
LINE POST AND SPACING

N.T.S.



DETAIL No.
500-2