



**GENERAL NOTES:**

1. WELD TOGETHER ALL ASSEMBLY BOLTS TO TENSION BANDS AND TENSION BANDS TO POSTS TO PREVENT DISASSEMBLY.

**CONSTRUCTION KEY NOTES:**

- A. 4" O.D. PIPE (9.11 LB./FT.)
- B. 1 7/8" O.D. PIPE (3.65 LB./FT.) GATE FRAME WELDED AT ALL JOINTS TO MAKE A SOLID FRAME
- C. 1 5/8" O.D. PIPE (2.27 LB./FT.)
- D. 3/8" DIA. TRUSS ROD WITH TRUSS TIGHTENER (TYP.)
- E. 2500 PSI CONCRETE
- F. POST CAP (TYP.)
- G. PLUNGER ROD LATCH, BOLTS WELDED TO PREVENT DISASSEMBLY
- H. HINGE ASSEMBLY, BOLTS WELDED TO PREVENT DISASSEMBLY
- I. 9 GA. GALVANIZED 2" CHAIN-LINK FABRIC
- J. BARBED TAPE, 24" COIL WITH 3 ROWS OF 3 STRAND BARBED WIRE
- K. 1 5/8" O.D. PIPE (2.27 LB./FT.) PLUNGER ROD
- L. 2 3/8" O.D. PIPE (3.65 LB./FT.) PLUNGER ROD GUIDE
- M. 2500 PSI CONCRETE COLLAR AROUND ROD GUIDE
- N. GRAVEL SUMP

STANDARD  
DETAIL

DATE: 4/1995  
REV: 11/11/2009

CHAIN-LINK FENCE  
DOUBLE SWING GATE

N.T.S.



DETAIL No.  
500-3