



**GENERAL NOTES:**

1. WELD TOGETHER ALL ASSEMBLY BOLTS TO TENSION BANDS AND TENSION BANDS TO POSTS TO PREVENT DISASSEMBLY.

**CONSTRUCTION KEY NOTES:**

- A. 4" O.D. PIPE (9.11 LB./FT.)
- B. 2" SQ. STEEL TUBE GATE FRAME WELDED AT ALL JOINTS TO MAKE A SOLID FRAME
- C. 1" SQ. STEEL TUBE BRACE (TYP.)
- D. 3/8" DIA. TRUSS ROD WITH TRUSS TIGHTENER (TYP.)
- E. 2500 PSI CONCRETE
- F. POST CAP (TYP.)
- G. FULCRUM LATCH
- H. HINGE ASSEMBLY, BOLTS WELDED TO PREVENT DISASSEMBLY
- I. 9 GA. GALVANIZED 2" CHAIN-LINK FABRIC STRETCHED & WELDED ON TO DOOR FRAME
- J. BARBED TAPE, 24" COIL WITH 3 ROWS OF 3 STRAND BARBED WIRE

STANDARD  
DETAIL

DATE: 4/1995  
REV: 11/11/2009

CHAIN-LINK FENCE  
PEDESTRIAN GATE

N.T.S.



DETAIL No.  
500-4