



**GENERAL NOTES:**

1. CLEANOUT TO BE USED AT END OF LINES & AT CUL-DE-SACS (AS SPECIFIED ON PLANS).
2. DOUBLE WYES TO BE USED AS NECESSARY ON CUL-DE-SACS.
3. SPOOL LENGTHS AND DEPTHS WILL VARY.
4. BONNET BOX & CONCRETE COLLAR TO BE FLUSH WITH FINISHED GRADE.
5. CLEANOUT NOT TO BE USED MORE THAN 300' AWAY FROM LAST MANHOLE IN LINE.

**CONSTRUCTION KEY NOTES:**

- A. 8" P.V.C. SDR 35 (LENGTHS VARY)
- B. 8" LONG SWEEP BEND 45°
- C. 3'x3'x6" CONCRETE COLLAR
- D. BONNET BOX (SEE DET 396)
- E. BONNET BOX COVER (SEE DET 397)
- F. 2500 PSI CONCRETE THRUST BLOCKING
- G. No. 5 REBAR HAIR PIN. PAINT UNEMBEDDED PORTION OF REBAR WITH TWO COATS OF COAL TAR EPOXY.

STANDARD  
DETAIL

DATE: 03-12-98  
REV: 03-25-98

END OF SEWER LINE CLEANOUT

N.T.S.



DETAIL No.  
395